

ITEM SPECIFICATION

Item Code : 2101717031
Unit : 04 METRE

Date : 19/12/2025

SERGE BATTLE DRESS POLY WOOL DARK DRAB 142 CMS WIDTH MIN
PROV. SPECIFICATION NO: S/5432/PW/TC-19(a), MIN WIDTH 142 CMS
ARE REQUIRED TO BE WATER REPELLANT & SHOULD CONFORM TO
STANDARD / VALUES LAID DOWN IN R/O THE BUNDESMANN TEST AS
MENTIONED IN CLAUSE 6.1 (a) OF ABOVE SPECIFICATION. TESTING
OF % COMPOSITION OF WOOL & POLYESTER SHOULD BE DONE AS PER
IS:2006-1988 SECOND REVISION AMENDMENT NO.1 & THE METHOD OF
CALCULATION TO BE BASED ON DRY MASS BASIS ONLY AS PER CLAUSE
9.4.1 OF SPECIFICATION, EXCEPT THAT

- 1) FIRM SHALL GET THEIR NAME WOVEN IN THE SELVEDGE WITH
FINER THREAD OF SAME COLOUR AT AN INTERVAL NOT EXCEEDING
30 CMS BETWEEN TWO MARKINGS.
- 2) WIDTH OF SELVEDGE SHALL NOT EXCEED 8 MM.
- 3) THE MANUFACTURER SHALL SUPPLY THE MATERIAL DULLY FLAGGED
FOR ALL TYPE OF DEFECTS.
- 4) PACKING & MARKING: AS PER CQA(T&C) KANPUR SCHEDULE NO.
CQA(T&C)/PMS/35(D), EXCEPT THAT
 - A) FABRIC IN ROLL FORM SHALL NOT BE LESS THAN 40 METERS
IN RUNNING LENGTH WITHOUT STITCHING/BASTING IN BETWEEN
 - B) ROLL WEIGHT SHALL NOT EXCEED 50 KGS.
 - C) EACH ROLL OF FABRIC SHALL BE WRAPPED SEPERATELY WITH
POLYPROPYLENE PLAIN SHEET. FINAL PACKING OF 2 ROLLS IN
ONE WATER PROOF GUNNY/HDPE SHEETS.
 - D) DIMENSIONS FOR PAPER TUBES OF FABRIC ROLL:
OUTER DIA - 3.5 CM, INNER DIA - 2.5 CM
THICKNESS - 0.5 CM.
 - E) FABRIC SELVEDGES SHALL BE WOUND EVENLY AT ONE EDGE.
- 5) SELVEDGES SHALL BE FIRM, STRAIGHT AND FRINGES IF ANY
SHALL NOT BE MORE THAN 5 MM.
- 6) SAMPLING PLAN: AS PER RELEVANT CLAUSE OF SPECIFICATION.

Remarks of Specification Modification

28/05/2014
14/06/2014
19/12/2025 LF COLOUR UPDATED VIDE R.NOTE 4706/T/ARMY/TARGET DT 18.12.25

28/05/2014
28/05/2014
28/05/2014